5300CE

Your high-capacity, high-volume ATM solution with 24/7 access.

The **5300CE** delivers the powerful financial transaction support you need with a Windows CE platform base. This high-volume ATM solution features high-capacity note storage and 24/7 customer access. This rugged model brings you the same high quality and proven dependability you expect from industry leader Nautilus Hyosung.

INNOVATIVE DESIGN

This latest advancement in customer convenience features a user-friendly interface displayed on a vivid 15" screen.

HIGH CAPACITY

The **5300CE** accommodates up to four 2,000-note cassettes for a maximum storage of 8,000 notes. The dispenser profile can be adjusted to suit your specific needs, making this the ideal solution for high-volume transactions.

EXTRA SECURITY

Experience peace of mind knowing the **5300CE's** high-volume of notes can be protected with a Level 1 safe option. The unique design also allows you to add an optional camera for added security.

EFFICIENCY

This cutting-edge model offers you a low cost, financial institute grade ATM that is Windows CE platform based.

TCP/IP with SSL SUPPORT

The **5300CE** includes built-in TCP/IP with Secure Socket Layers (SSL) for enhanced security while connected to the Internet.

RELIABILITY

You can count on the **5300CE**. Its ease of maintenance and simplified service provide maximum availability and uptime with minimal operational intervention.



System Platform

■ Microsoft® Windows® CE 5.0

Card Reader

- Dip type card reader
- IC Card Reader (optional)

Communication

■ TCP/IP, dial-up

Screen Display

- 15"color TFT LCD
- Privacy filter (optional)

Power Supply

■ AC 110-240 V, 50-60 Hz

Security

- UL291 business hour safe
- Electronic lock (standard)
- KABA Mas Cencon lock, S&G lock (optional)
- Level1 safe (optional)

Printers

Graphic thermal receipt printer



Cash Dispenser

- 2,000 note cassette
- Up to 8,000 notes (optional) upgradable to four cassettes

Input Type

- 4x2 function keys
- PCI EPP (Encrypting Pin Pad)
- ADA Compliant
- RKT (optional)

Additional Features

- Flicker
- Audio jack
- Topper (optional)
- EPP illumination
- Retractable door handle
- Speaker
- Braille keypad
- Electronic journal
- Supports three languages: English, Spanish, French
- Enhanced Standard 1 (Hyosung Standard)

Environmental Conditions

■ Temperature: 0°C~ 40°C (28°F – 104°F)

■ Humidity: 20 ~ 85%

Dimensions

Height: 54.4" (1,382 mm)
Width: 18.1" (460 mm)
Depth: 25.4" (644 mm)
Weight: 617 lbs. (280 kg)

^{*}Subject to note quality and other variables



Contact your authorized Nautilus Hyosung distributor or representative for more information.

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.







